



M3 5,000 BTU INFRARED RADIANT HEATER



Gasolec M3 Infrared Heater

Pictured above is Gasolec's M3 Infrared Heater. Operating gas pressures range from 0.3 to 4.5 psi, providing up to 5,425 BTU's. The M3 is available with a standard stainless steel filter, (pictured above) or an optional heavy duty filter. The advantages of the M3 make it the preferred available in both LP and Natural Gas. Contact your local supplier, or visit our website at www.gasolecusa.com for additional information on the M3 and all of our quality products.

- + Stainless Steel Construction**
- + Lightweight**
- + Low Maintenance**
- + Wide Operating Range**
- + Fuel Savings**
- + Reliability**



Infrared Advantages

Unlike other forms of heating that use significant amounts of energy to heat the entire cubic volume of a building, infrared heat allows you to concentrate the heat directly to the animals and the floor. You will benefit from lower fuel cost without sacrificing animal comfort. In fact, beneath the “cone of infrared,” your animals can find their own individual comfort zones resulting from the heating patterns projected by the M3. The M3 is of stainless steel construction and can withstand high pressure washouts and reasonable abuse. With no moving parts, the simple, straight forward design of Gasolec’s M3 Infrared Heaters lead to low maintenance and easy service. The advantages of the M3 clearly make it a preferred choice in the animal confinement industry.

Gasolec has made the M3 available in both propane and natural gas versions.

*Gasolec M3 LP 20-310 Infrared Heater
Specifications*

Capacity	
Maximum Btu/hr	5,425 Btu/hr
Maximum Watt/hr	1,500 Watt/hr
Consumption (Liquid Propane)	
Liq.Gal/hr	0.06
Supply Pressure	4.5 p.s.i.
Physical Size	
Length	14 in.
Width	8.5 in.
Height	6 in.
Weight	1.9 lb.
Installation Height	26-36 in.
Minimum Clearance to Combustibles	
Top	24 in.
Side	24 in.
Below	24 in.