

DIRECT FIRED
 LP/ LPG
 SPACE HEATER



ADVANTAGES V. FURNACES

- +

 High cfm air flow; fewer heaters needed
- +

 Fuel saving, adjustable heat output

- High heat / Low heat / Fan only mode

 - Fan only mode for ventilation
- +

 Low CO, NOx, & Ethylene emissions
- +

 Wash-down capable

- Electric board IP65 rated

 - IP55 rated motor
- +

 Thermostat or climate controller ready
- +

 Safety

- Flame monitoring ionization electrode

 - Overheat thermostat control
- +

 High grade 430 stainless steel construction

OTHER FEATURES

- +

 Automatic, direct spark ignition
- +

 EN Certified

ITEM #: F130104	MODEL: GA1634
Max heat output	100.4 kW • 343,000 BTU/hr
Min heat output	47.4 kW • 163,000 BTU/hr
Max fuel consumption	6.7 kg/hr • 14.7 lbs/hr
Min fuel consumption	3.2 kg/hr • 6.6 lbs/hr
Gas pressure	0.4 - 1.5 mBar • 5.8 - 21.8 PSI
Heat efficiency	99.9%
Air flow	5.1 m³/h • 3.0 cfm
Air temperature	75° C • 167°F
Power consumption	600 W • 230V
Electrical power	230V 1 phase 50 Hz
Heater Dimensions [l x w x h]	11.5 x 6.0 x 4.5 cm • 45.1 x 23.2 x 17.4 in



F150035
 Thermostat with Remote



F130114
 Adapter Duct



F130124
 4 in x 12 ft Flexible Duct